

Excellence in seaming



1295/1296

Single-needle and double-needle
lockstitch postbed sewing machine
with unison feed

1295 1296

Top-stitching and assembly seams on three-dimensional parts in the home upholstery- and automotive industry









Features:

- Unobstructed view of the stitching area
- The postbed design is ideal for handling shaped parts before or after they are closed
- Trouble-free stitching over cross-seams with no difference in stitch length, due to the alternating top feed with 7 mm stroke
- Accurate and consistent stitch formation on all materials, up to thread sizes of 15/3-ply, synth.
- Uncomplicated mechanical system guarantees perfect function
- Built-in bobbin winder within operator's view
- Large vertical hook with 60% more thread capacity than conventional hooks
- Protection of the hook against thread jamming by built-in and easy-to-handle overload clutch as standard equipment
- High sewing output and easy operation due to time- and cost-saving work aids, such as:
 - Thread trimmer
 - Automatic presser foot lift
 - Backtacking mechanism
 - Needle positioning mechanism
- Large fabric clearance of 10 mm for easier loading and removal of the workpiece
- As an alternative available with a long stitch (up to 11 mm) for rustic stitching
- Machines with subclass -911/97 and -900/56 are equipped with new drive technology P40CD



PFAFF

Versions:

Type	Model									Four-motion drop feed
		-6/01	-63/15		-900/56		-911/97			P
1295	C	●			6,0				-	●
1295	C	●			11,0				-	●
1295	C	●			6,0	●	●	●	-	●
1296*	C		●		6,0				6,0; 8,0; 10,0	●
1296*	C		●		6,0		●	●	6,0; 8,0; 10,0	●
1296*	C		●		6,0	●	●	●	6,0; 8,0; 10,0	●
1296	C				11,0		●	●	6,0; 8,0; 10,0	●
1296	C			●	11,0		●	●	6,0; 8,0; 10,0	●

Remarks:

-6/01: For plain seaming operations

-63/15: Fancy- and top-stitching operations, also on one-sided bulky cross-seams; compensating presser, pneumatically operated, engageable middle seam guide and tape guide from below

-900/56: Thread trimmer solenoid-controlled

-911/97: Automatic backtacking mechanism with additional quick button on machine head for backtack inside seams and automatic roller presser lifter.

* also without part set available

** on request



Technical data:

Stitch type:

301 (lockstitch)

Max. speed:

1,900

Top feed lift:

7 mm

Fabric clearance:

10 mm

Needle system: 134-35**Needle size:**

(Nm in 1/100 mm)
110-150

Balance wheel.:

90 mm

Motor power:

PFAFF P40 CD: 500 W (1295/1296 with -900, -911)

Ho Hsing MJ-1: 600 W (1295/1296 without -900, -911)

Clear work space:

270 x 165 mm

Bed plate dimensions:

518 x 177 mm

Net weight: (sewing head)

approx. 57 kg

Gross weight:

(sewing head in carton)
approx. 67 kg

**PFAFF Industriesysteme
und Maschinen GmbH**

Hans-Geiger-Str. 12 – IG Nord

D-67661 Kaiserslautern

Telefon: +49-6301/3205-0

Telefax: +49-6301/3205-3171

E-mail: info@pfaff-industrial.com

Website: www.pfaff-industrial.com